

AC6084A Datasheet

Zhuhai Jieli Technology Co.,LTD

Version: V1.0

Date: 2020.10.13

Copyright © Zhuhai Jieli Technology Co.,LTD. All rights reserved.

AC6084A Features

CPU

- 32-bit DSP supports hardware Float Point Unit (FPU)
- Up to 160MHz programmable processor
- 64Vectored interrupts
- 4 Levels interrupt priority

DSP Audio Processing

- Supports MP2, MP3, WMA audio decoding
- 10-band EQ configuration for voice Effects
- Built-in microphone echo function

Audio Codec

- Two channels 16-bit DAC, SNR \geq 92dB
- One channels 16-bit ADC , SNR \geq 90dB
- Sampling rates of 8KHz/11.025KHz/16KHz/22.05KHz/24KHz/32KHz/44.1KHz/48KHz are supported
- One analog MIC amplifier, build-in MIC bias generator
- Two channels Mono analog MUX
- Supports cap-less, single-ended, and differential mode at the DAC path
- Supports 16ohm and 32ohm Speaker loading

Peripherals

- Full speed USB 2.0 OTG controller

- Multi-function 32-bit timers, support capture and PWM mode
- Three full-duplex basic UART, UART0 and UART1 supports DMA mode
- Two SPI interface supports host and device mode
- One hardware IIC interface supports host and device mode
- 10-bit ADC for analog sampling
- External wake up/interrupt on all GPIOs

PMU

- Low voltage LDO for internal digital and analog circuit supply
- 3uA current consumption in the soft-off mode
- Built-in LDO for the core, I/O and flash
- VBAT is 2.2V to 5.5V
- VDDIO is 2.2V to 3.6V

Packages

- QSOP24

Temperature

- Operating temperature: -40°C to +85°C
- Storage temperature: -65°C to +150°C

Applications

- Card MP3 player speaker

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

1、 Pin Definition

1.1 Pin Assignment




Figure 1-1 AC6084A_QSOP24 Package Diagram

1.2 Pin Description

Table 1-1 AC6084A_QSOP24 Pin Description

PIN NO.	Name	I/O Type	Drive (mA)	Function	Other Function
1	PA1	I/O	24/8	GPIO	MIC: MIC Input Channel ; ADC1: ADC Input Channel 1; PWM4: Timer4 PWM Output; UART1RXC: Uart1 Data In(C);
2	PA0	I/O	24/8	GPIO	SDPG: SD Power Supply; ADC0: ADC Input Channel 0; CLKOUT0; UART1TXC: Uart1 Data Out(C);
3	AGND	P	/		Analog Ground
4	VCOM	P	/		DAC Reference
5	DACL	O	/		DAC Left Channel
	DACR	O	/		DAC Right Channel
6	PB7	I/O	24/8	GPIO	SD0CLK_B: SD0 Clock(B); SD0CLK_F: SD0 Clock(F); SPI2DOA: SPI2 Data Out(A); AMUX1R: Analog Channel1Right; IIC_SDA_C: IIC DAT(C); ADC9: ADC Input Channel 9; PWM5: Timer5 PWM Output; UART1RXA: Uart1 Data In(A);
7	PB6	I/O	24/8	GPIO	SD0CMD_B: SD0 Command(B); SD0CMD_F: SD0 Command(F); SPI2CLKA: SPI2 Clock(A); AMUX1L: Analog Channel1 Left; IIC_SCL_C: IIC SCL(C); ADC8: ADC Input Channel 8; TMR3: Timer3 Clock Input; UART1TXA: Uart1 Data Out(A);
8	PB4	I/O	24/8	GPIO	SD0DAT_F: SD0 Data(F); ADC7: ADC Input Channel 7; LVD: Low Voltage Detect; UART2TXC: Uart2 Data Out(C); UART2RXC: Uart2 Data In(C); CLKOUT1; Q-decoder2_0;

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

9	VSSIO	P	/		IO Ground
10	LDOIN	P	/		Battery Charger In
	PB5	I/O	8	GPIO (High Voltage Resistance)	SD0DAT_B: SD0 Data(B); SPI2DIA: SPI2 Data Input(A); PWM3: Timer3 PWM Output; CAP1: Timer1 Capture; UART0TXC: Uart0 Data Out(C); UART0RXC: Uart0 Data In(C); Q-decoder2_1;
11	VBAT	P	/		Battery Power Supply
12	VDDIO	P	/		IO Power 3.3v
13	PB3	I/O	24/8	GPIO	SD0DAT_D: SD0 Data(D); ADC6: ADC Input Channel 6; PWM2: Timer2 PWM Output; UART2RXB: Uart2 Data In(B); Q-decoder1_1;
14	PB2	I/O	8	GPIO (High Voltage Resistance)	SD0CMD_D: SD0 Command(D); SPI1DIA: SPI1 Data In(A); UART2TXB: Uart2 Data Out(B); CAP0: Timer0 Capture; Q-decoder1_0;
	PB1	I/O	24/8	GPIO	Long Press Reset; SPI1DOA: SPI1 Data Out(A); ADC5: ADC Input Channel 5; UART0RXB: Uart0 Data In(B); TMR2: Timer2 Clock Input;
15	PB0	I/O	8	GPIO (High Voltage Resistance)	SD0CLK_D: SD0 Clock(D); SPI1CLKA: SPI1 Clock(A); UART0TXB: Uart0 Data Out(B); TMR5: Timer5 Clock Input;
16	PC5	I/O	24/8	GPIO	SD0CLK_A: SD0 Clock(A); SD0CLK_E: SD0 Clock(E); SPI1DOB: SPI1 Data Out(B); IIC_SDA_B: IIC SDA(B); ADC12: ADC Input Channel 12; TMR1: Timer1 Clock Input; UART2RXD: Uart2 Data In(D);

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

17	PC4	I/O	24/8	GPIO	SD0CMD_A: SD0 Command(A); SPI1CLKB: SPI1 Clock(B); IIC_SCL_B: IIC SCL(B); ADC11: ADC Input Channel 11; PWM1: Timer1 PWM Output; UART2TXD: Uart2 Data Out (D);
18	PC3	I/O	24/8	GPIO	SD0DAT_A: SD0 Data(A); SPI1DIB: SPI1 Data In(B); CAP2: Timer2 Capture; UART0TXD: Uart0 Data Out (D); UART0RXD: Uart0 Data In(D);
19	PC2	I/O	24/8	GPIO	ADC10: ADC Input Channel 10; CAP5: Timer5 Capture; UART1RXB: Uart1 Data In(B);
20	USBDM	I/O	4	USB Negative Data (pull down)	SD0DAT_E: SD0 Data(E); SPI2DOB: SPI2 Data Out(B); IIC_SDA_A: IIC SDA(A); ADC14: ADC Input Channel 14; UART1RXD: Uart1 Data In(D);
21	USBDP	I/O	4	USB Positive Data (pull down)	SPI2CLKB: SPI2 Clock(B); IIC_SCL_A: IIC SCL(A); ADC13: ADC Input Channel 13; UART1TXD: Uart1 Data Out(D);
22	PA4	I/O	24/8	GPIO	SD0CMD_C: SD0 Command(C); SD0CMD_E: SD0 Command(E); AMUX0R: Analog Channel0 Right; UART1_RTS: Uart1 Request to send; ADC3: ADC Input Channel 3; TMR4: Timer4 Clock Input; UART2RXA: Uart2 Data In(A); Q-decoder0_1;
23	PA3	I/O	24/8	GPIO	SD0DAT_C: SD0 Data(C); AMUX0L: Analog Channel0 Left; ADC2: ADC Input Channel 2; UART1_CTS: Uart1 Clear to send; UART2TXA: Uart2 Data Out(A); PWM5: Timer5 PWM Output; Q-decoder0_0;
24	PA2	I/O	24/8	GPIO	SD0CLK_C: SD0 Clock(C); MIC_BIAS: Microphone Bias Output; CAP3: Timer3 Capture;

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2、Electrical Characteristics

2.1 Absolute Maximum Ratings

Table 2-1

Symbol	Parameter	Min	Max	Unit
Tamb	Ambient Temperature	-40	+85	°C
Tstg	Storage temperature	-65	+150	°C
VBAT	Supply Voltage	-0.3	5.5	V
V _{3.3IO}	3.3V IO Input Voltage	-0.3	3.6	V
LDOIN	Charge Input Voltage	-0.3	6.0	V

Note : The chip can be damaged by any stress in excess of the absolute maximum ratings listed below

2.2 PMU Characteristics

Table 2-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
LDOIN	Loading current	–	–	250	mA	VBAT = 4.2V
VBAT	Voltage Input	2.2	3.7	5.5	V	–
V _{VDDIO}	Voltage output	–	3.3	–	V	VBAT = 4.2V, 100mA loading

2.3 Battery Charge

Table 2-3

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
LDOIN	Charge Input Voltage	4.5	5	5.5	V	–
V _{Charge}	Charge Voltage	4.15	4.2	4.25	V	–
I _{Charge}	Charge Current	20	–	250	mA	Charge current at fast charge mode
I _{Trickl}	Trickle Charge Current	20	45	70	mA	V _{BAT} < V _{Trickl}

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.4 IO Input/Output Electrical Logical Characteristics

Table 2-4

IO input characteristics						
Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
V _{IL}	Low-Level Input Voltage	-0.3	–	0.3* VDDIO	V	VDDIO = 3.3V
V _{IH}	High-Level Input Voltage	0.7* VDDIO	–	VDDIO+0.3	V	VDDIO = 3.3V
IO output characteristics						
V _{OL}	Low-Level Output Voltage	–	–	0.33	V	VDDIO = 3.3V
V _{OH}	High-Level Output Voltage	2.7	–	–	V	VDDIO = 3.3V

2.5 Internal Resistor Characteristics

Table 2-5

Port	General Output	High Drive	Internal Pull-Up Resistor	Internal Pull-Down Resistor	Comment
PA0~PA4 PB1,PB4 PB6,PB7 PC2~PC5	8mA	24mA	10K	10K	1、PB1 default pull up 2、USBDM & USBDP default pull down 3、internal pull-up/pull-down resistance accuracy ±20%
PA0 PB3	Output 0	8mA	10K	10K	
	Output 1	8mA			
PB0,PB2,PB5	8mA	–	10K	10K	
USB DP	4mA	–	1.5K	15K	
USB DM	4mA	–	180K	15K	

2.6 DAC Characteristics

Table 2-6

Parameter	Min	Typ	Max	Unit	Test Conditions
Frequency Response	20	–	20K	Hz	1KHz/0dB 10Kohm loading With A-Weighted Filter
THD+N	–	-72	–	dB	
S/N	–	92	–	dB	
Crosstalk	–	-80	–	dB	
Output Swing	–	1	–	V _{rms}	
Dynamic Range	–	90	–	dB	1KHz/-60dB 10Kohm loading With A-Weighted Filter
DAC Output Power	11	–	–	mW	32ohm loading

2.7 ADC Characteristics

Table 2-7


Parameter	Min	Typ	Max	Unit	Test Conditions
Dynamic Range	–	80	–	dB	1KHz/-60dB
S/N	–	90	91	dB	1KHz/-60dB
THD+N	–	-70	–	dB	
Crosstalk	–	-90	–	dB	

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

3、 Package Information

3.1 QSOP24



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	—	—	1.75
A1	0.10	0.15	0.25
A2	1.30	1.40	1.50
A3	0.60	0.65	0.70
b	0.23	—	0.31
b1	0.22	0.25	0.28
c	0.20	—	0.24
c1	0.19	0.20	0.21
D	8.55	8.65	8.75
E	5.80	6.00	6.20
E1	3.80	3.90	4.00
e	0.635BSC		
h	0.30	—	0.50
L	0.50	—	0.80
L1	1.05REF		
θ	0	—	8°

Figure 3-1. AC6084A_QSOP24 Package

4、 Revision History

Date	Revision	Description
2020.10.13	V1.0	Initial Release

Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.